



# TECHNICAL SHEET



FA 20 400 25


## Designation: Retractable Fall Arrester Olympe in wire rope

- Steel wire rope diam. 4.8 mm.
- Casing made up of high impact strength Polymer to prevent breakage and nearly indestructible.
- Swivel at the top and at the bottom of the device.
- Lateral carrying handle.
- Minimum breaking strength: > 12kN.
- Rubber protective snout for manipulating the cable.

**Connectors:** 1 screw-locking karabiner, opening 17 mm, ref. FA 50 101 17 et 1 snap hook with swivel and fall indicator, opening 21 mm.

**Compliance:** Conforms to EN360:2002.

Certified for a horizontal use when used with the lanyard ref. FA 40 304 15 connected to the wire rope of the block.



**Length:** 25 mtrs.

## Material of the components:

Polymer casing: PA 6 30% fiberglass.

Wire rope: Galvanized steel.

Connectors: Steel.

**HS code**

84289090

**Carton size / Pieces**

80x40x24 / 2

**Unit weight**

12.32 Kg

## AET : N° 5158 Issue 2 Extension 1

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

## Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 01/15

**ZI les portes du Dauphiné**

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

